
EVERETT STEEL COMPANIES

6063-T6 EXTRUDED ALUMINUM PIPE

Schedule 40 – 20 Ft. Lengths

ASTM B-241

Nominal Size	OD Inches	ID Inches	Wall Thickness Inches	Wt. per Lin. Ft.	Wt. per Length
1/2	.840	.622	.109	.294	5.88
3/4	1.050	.824	.113	.392	7.84
1	1.315	1.049	.133	.581	11.62
1-1/4	1.660	1.380	.140	.786	15.72
1-1/2	1.900	1.610	.145	.940	18.80
2	2.375	2.067	.154	1.264	25.28
2-1/2	2.875	2.469	.203	2.004	40.08
3	3.500	3.068	.216	2.621	52.42
3-1/2	4.000	3.548	.226	3.152	63.04
4	4.500	4.026	.237	3.733	74.66
5	5.563	5.047	.258	5.057	101.14
6	6.625	6.065	.280	6.564	131.28

6061-T6 EXTRUDED STRUCTURAL ALUMINUM PIPE

Schedule 40 – 20 Ft. Lengths

ASTM B-429

Nominal Size	OD Inches	ID Inches	Wall Thickness Inches	Wt. per Lin. Ft.	Wt. per Length
3/4	1.050	.824	.113	.392	7.84
1	1.315	1.049	.133	.581	11.62
1-1/4	1.660	1.380	.140	.786	15.72
1-1/2	1.900	1.610	.145	.940	18.80
2	2.375	2.067	.154	1.264	25.28
2-1/2	2.875	2.468	.203	2.004	40.08
3	3.500	3.068	.216	2.621	52.42
3-1/2	4.000	3.548	.226	3.152	63.04
4	4.500	4.026	.237	3.733	74.66
5	5.563	5.047	.258	5.057	101.14

(continued)

**ALUMINUM COUPLINGS AND ELBOWS AVAILABLE.
CALL FOR PRICES.**

EVERETT STEEL COMPANIES

6061-T6 EXTRUDED STRUCTURAL ALUMINUM PIPE

(Continued)

Nominal Size	OD Inches	ID Inches	Wall Thickness Inches	Wt. per Lin. Ft.	Wt. per Length
6	6.625	6.065	.280	6.564	131.28
8	8.625	7.981	.322	9.878	197.56
10	10.750	10.020	.365	14.000	280.00
12	12.750	12.000	.375	17.140	342.80

6061-T6 EXTRUDED ALUMINUM PIPE

Schedule 80 - 20 Ft. Lengths

ASTM B-241

Nominal Size	OD Inches	ID Inches	Wall Thickness Inches	Wt. per Lin. Ft.	Wt. per Length
1	1.315	.957	.179	.751	15.02
1-1/4	1.660	1.278	.191	1.037	20.74
1-1/2	1.900	1.500	.200	1.256	25.12
2	2.375	1.939	.218	1.737	34.74
2-1/2	2.875	2.323	.276	2.650	53.00
3	3.500	2.900	.300	3.547	70.94
3-1/2	4.000	3.364	.318	4.326	86.52
4	4.500	3.826	.337	5.183	103.66
5	5.563	4.813	.375	7.188	143.76
6	6.625	5.761	.432	9.884	197.68
8	8.625	7.625	.500	15.010	300.20
