
EVERETT STEEL COMPANIES

6063-T6 SQUARE EXTRUDED ALUMINUM TUBE

Sharp Corners - 21'1" Lengths

Size	Wall Thickness	Wt. per Lin. Ft.	Wt. per Length
3/4	.062	.205	4.32
3/4	.125	.375	7.91
1	.062	.279	5.88
1	.125	.526	11.09
1-1/4	.125	.676	14.25
1-1/2	.125	.826	17.41
1-3/4	.125	.975	20.56
2	.125	1.126	23.74
3	.125	1.725	36.37
4	.125	2.325	49.02

6061-T6 SQUARE EXTRUDED ALUMINUM TUBE

Round Corners - 20' Lengths

Size	Wall Thickness	Wt. per Lin. Ft.	Wt. per Length
2	.250	2.10	42.00
3	.250	3.234	64.68

6063-T6 RECTANGULAR EXTRUDED ALUMINUM TUBE

Sharp Corners - 21'1" Lengths

		.676	14.25
		.826	17.41
Size	Wall Thickness	Wt. per Lin. Ft.	Wt. per Length
1/2 x 1	.125	.375	7.91
3/4 x 1-1/2	.125	.600	12.65
1 x 1-1/2	.125	.675	14.23
1 x 2	.125	.825	17.39
1-1/4 x 2-1/2	.125	1.050	22.14
1-1/2 x 2	.125	.975	20.56
1-3/4 x 3	.125	1.350	28.46
1-3/4 x 4	.125	1.650	34.79
2 x 3	.125	1.426	30.06
2 x 5	.125	2.025	42.69
2 x 6	.125	2.326	49.04
3 x 5	.125	2.325	49.02
3 x 6	.188	3.892	82.06