
EVERETT STEEL COMPANIES

HOT ROLLED STRIP

ASTM A-36



| Size | Weight in Pounds | |
|-------------|------------------|---------|
| | Per Foot | 20' Bar |
| 1/8 x 1/2 | .213 | 4.26 |
| (.125) 3/4 | .319 | 6.38 |
| 1 | .425 | 8.50 |
| 1-1/4 | .531 | 10.62 |
| 1-1/2 | .638 | 12.76 |
| 1-3/4 | .744 | 14.88 |
| 2 | .850 | 17.00 |
| 2-1/2 | 1.063 | 21.26 |
| 3 | 1.275 | 25.50 |
| 3-1/2 | 1.488 | 29.76 |
| 4 | 1.700 | 34.00 |
| 5 | 2.125 | 42.50 |
| 6 | 2.550 | 51.00 |
| 8 | 3.400 | 68.00 |
| 3/16 x 1/2 | .319 | 6.38 |
| (.1875) 3/4 | .478 | 9.56 |
| 1 | .638 | 12.76 |
| 1-1/4 | .797 | 15.94 |
| 1-1/2 | .956 | 19.12 |
| 2 | 1.280 | 25.60 |
| 2-1/2 | 1.590 | 31.80 |
| 3 | 1.910 | 38.20 |
| 3-1/2 | 2.230 | 44.60 |
| 4 | 2.550 | 51.00 |
| 5 | 3.190 | 63.80 |
| 6 | 3.830 | 76.60 |
| 7 | 4.460 | 89.20 |
| 8 | 5.100 | 102.00 |
| 9 | 5.740 | 114.80 |
